



# MORBARK

► M12R ◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER



📞 **1300 072 926** | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)

**VIC** 24-28 Williams Road Dandenong Sth. 3175  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)  
**F** (03) 9791 7676

**NSW** Unit 1/21 Penny Place Arndell Park 2148  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)  
**F** (02) 8678 2478



# MORBARK® BEEVER™ M12R



## BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all Morbark equipment, the M12R is a long-lasting, durable machine backed by a world-class parts and service support team.




### Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labour.



### Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



### Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 4,911 kg/m of combined material pulling force.



### 360° Hydraulic Chute

Full 360° hydraulic chute with swivel discharge and adjustable height puts chips right where they're needed without removing the Beever from the tow vehicle.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

### General

Chipping capacity .....	12" (30.5 cm)
Height .....	256.5 cm
Width .....	180.3 cm
Length .....	469.9 cm
Weight (approximate) .....	2,494.8 kgs
Suspension .....	2,721 kgs
Infeed opening .....	60" wide x 31" high
Throat opening .....	15" wide x 14" high
Drum .....	14.5" wide x 21.375" diameter
Engine .....	CAT Diesel
Horsepower .....	114 HP
Fuel capacity .....	92.7 litres
Hydraulic capacity .....	64.4 litres
Frame .....	3.72 kgs, 15.24 cm channel
Tyres .....	(2) 235/80R16"
Hitch .....	63.5 mm Pintle Ring

### Equipment Highlights

14.5" wide x 21.375" diameter staggered-knife pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system.

Top and bottom horizontal feed wheels equipped with serrated teeth and knife bars.

Reversing automatic feed system.

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment.

Fuel tank sight gauge, drain plug and shutoff valve.

Hydraulic tank shut-off valve, drain plug and clean-out cover.

Live hydraulics; ball valve, pump, motor and control valve.

7.6 cm x 12.7 cm tubular steel telescoping drawbar with two 30.5 cm extensions.

### Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

### Options Include

ChipSafe® Operator Safety Shield

Folding Infeed Tray

Winch package: heavy-duty, 2,268 kgs pull capacity with rope and 305cm chafe guard

Custom paint and logo packages

Hydraulic Swivel Discharge

Cone Holder

Flow Control

Axle Options Available

Fender Options Available

Battery Box Options Available

Fender Options Available



# MORBARK



1300 072 926 | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)