



MORBARK[®]
BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

▶ M15RX ◀◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER



📞 **1300 072 926** | globalmachinerysales.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
E sales@globalmachinerysales.com.au
F (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148
E sales@globalmachinerysales.com.au
F (02) 8678 2478

MORBARK® BEEVER™ M15RX



BENEFITS

- With its high capacity and lighter weight design, this compact chipper is the ideal unit for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- Hydra-Lift top feed wheel compression system with spring-assisted down pressure provides more than 1,500 lbs. (680 kgs) of material crushing power.
- Like all Morbark equipment, the M15RX is a long-lasting, durable machine backed by a world-class parts and service support team.



TorqMax™ Feed System Infeed System

The powerful TorqMax™ top feed wheel compression system generates more than 5,060 kg/m of material pulling force.

The wide infeed opening with 45.7cm diameter single top feed wheel and straight flow-through infeed easily climbs over material, reduces drag and increases chipping efficiency.

Channel Frame

The 3.72kgs, 15.24cm channel frame rails with 5.08cm x 15.24cm tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.

360° Swivel Discharge

360° manual crank swivel discharge with adjustable height puts chips right where they're needed without removing the Beever from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Chipping capacity	15" (38.1 cm)
Height	269.2 cm
Width	210.8 cm
Length	500.4 cm
Weight (approximate)	3,265.9 kgs
Suspension	3,175 kgs
Infeed opening	141 cm wide x 86.4 cm high
Throat opening	52 cm wide x 40.6 cm high
Drum	60.3 cm wide x 54.3 cm diameter
Engine	CAT Diesel
Horsepower	142 HP
Fuel capacity	121.13 litres
Hydraulic capacity	49.21 litres
Frame	3.72 kgs, 15.24 cm channel
Tyres	(2) 215/75R17 1/2"
Hitch	63.5 mm Pintle Ring

Equipment Highlights

60.3cm wide x 54.3cm diameter staggered-knife pocket drum with two dual-edged chipper knives and dual-sided, chambered air impeller systems.

Single (top) horizontal feed wheel with TorqMax top feed wheel compression system, hydraulic lift assist, spring assisted down pressure and manually applied hydraulic down pressure at the valve handle.

Reversing automatic feed system.

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment.

Fuel tank sight gauge, drain plug and shutoff valve.

Hydraulic tank shut-off valve, drain plug and clean-out cover.

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

Options Include

ChipSafe® Operator Safety Shield
 Winch package: heavy-duty, 2,268 kgs pull capacity with rope and 305cm chafe guard
 Custom paint and logo packages
 Bottom Bump Bar
 Hydraulic Swivel Discharge
 Cone Holder
 Spare Tyre/Mount
 Folding Infeed Tray
 Bottom Feedwheel
 Flow Control
 Axle, Fender and Battery Box Options Available



MORBARK
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES



1300 072 926 | globalmachinerysales.com.au