

"Built for the Tree Professional"

cmc[®]
AERIAL PLATFORMS

S15
ARBOR PRO



Safer, non-slip outrigger pads



**New
Arborist
saw
holder**

📞 1300 072 926

VIC 24-28 Williams Road Dandenong Sth. 3175
E vic@globalmachinerysales.com.au
F (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148
E nsw@globalmachinerysales.com.au
F (02) 8678 2478



globalmachinerysales.com.au | cmclifts.com.au



Designed for one of the roughest industries on this planet - the tree industry. This very simple lift is a winner for outdoor use.

With compact dimensions, the CMC S15 Arbor Pro (now available with safer, non-slip outrigger pads and a new arborist saw holder) is the most compact and lightest tracked aerial platform in this size. Whilst extremely compact, the S15 Arbor Pro is a mini giant when it comes to load, reach and stability, outperforming competitive lifts with an impressive 14.9m working height and 6.9m outreach, in a very compact stabilisation area of only 2.7m x 2.7m.

Built with a double pantograph lower boom, articulated upper boom with one telescopic boom extension, plus an articulating jib. Proportional electro hydraulic controls in the basket allow for a smooth, comfortable and safe ride for the operator. For ground travel, proportional controls on a cabled remote control allow for easy travel and safer loading and unloading operation.

Equipped standard with a quick connect, triple safety basket lock, the uniquely shaped "corner less" basket means better work versatility in difficult work locations. Quiet Honda engine/240v electric hydraulic power pack is standard. Also available with hybrid power source.





**Single Doorway
width (780mm)**




**Simple Control
System**



**Hydraulic
Extending Tracks**



**Towable
Transportable**



**OPTIONAL Dual
Voltage AC Motor**



**OPTIONAL Kubota
Diesel Engine**



Simple to use

User-friendly, with intuitive 4-step operation from start to working at height.

Versatile

Articulating boom, with telescopic and jib. Impressive height and basket outreach.

Service friendly

Simple operating system with fault code diagnosis and easy to repair on-site.

Compact

The most compact dimensions of any Spiderlift in this height range.

Power

11.7hp Honda GX390 Petrol engine with 240v 15amp 2.2kw AC motor.

Towable

Low weight and compact, so suitable to tow on a trailer behind mid-size vans and 4x4s.

PERFORMANCE

Max working height	14.9m
Max working outreach	6.9m
Max basket capacity	200kg
Jib movement	90°
Turret rotation	356°
(P) Max slope to stabilise	7° / 12%
Tracks extension/retraction	0.30m
(W) Max angle approach	13° / 23%
(X) Max travel slope	17° / 30%
Max travel speed	1.5km/h

DIMENSIONS

(A) Basket height	1.10m
(B) Basket width	0.70m
(C) Basket length	1.20m
(D) Total length	4.12m
(E) Total length without basket	3.50m
(F) Height in driving position	1.97m
(G) Total width (without basket)	0.78m
(H) Free height from the ground	0.34m
Tracks (LxW)	1.21 x 0.18m
(J) Maximum longitudinal stabilisation	2.7m
(K) Maximum cross stabilisation	2.7m
Stabilisers plate	0.18m

WEIGHTS

Total weight (Honda engine)	1,960kg
Total weight (Kubota engine)	2,060kg
Max pressure on the foot	4.54kg/cm ²
Max pressure on the track	0.21kg/cm ²
Max pressure in travel	312kg/m ²
Max pressure in work	246kg/m ²

POWER

Engine	8hp Honda GX390 Petrol
Electric motor	240v 15amp 2.2kw

