

RAYCO FEATURES



1 Hydrostatic Cutter Wheel Drive with Quick Stop. The two-piece cutter boom design keeps the engine level and allows the cutting depth to remain constant.

2 Swing-out operator station with protective polycarbonate window and full length rubber curtain.

3 Telescoping tongue with a 60-inch extension and adjustable hitch height.



RG74DXH SPECIFICATIONS

GENERAL	US	METRIC
Weight	5,920 lb	2,685 kg
Length	190"	508 cm
Height	97"	229 cm
Width	83"	218 cm
Chip Collection Capacity	86 cu ft	2,435 L
ENGINE		
Model	Cummins 3.8L, Diesel	Cummins 3.8L, Diesel
Gross HP	74 hp	55 kW
Fuel Tank Capacity	24 gal	91 L
HYDRAULIC SYSTEM		
Oil Tank Capacity	24 gal	91 L
CUTTING WHEEL		
Wheel Diameter	28"	71.12 cm
Wheel Thickness	1"	2.54 cm
Cutter Teeth Quantity	40 Super Tooth®	40 Super Tooth®
CUTTER RANGE		
Below Ground Level	26"	66 cm
Above Ground Level	31"	78.7 cm
Cutting Width	99.6"	253 cm



LED Trailer Lighting



Torflex Suspension Axle with (2) 235-75R-17.5H 6000 lb tires

Rayco Manufacturing Inc. retains the right to make changes in design and specifications; engineering; add or remove features; add improvements; or discontinue manufacturing at any time without notice or obligation. All claims and statements on this document are not legally binding, and are subject to change. No legal obligations can be derived from this document.

