



MORBARK®

► Beaver 1215 ◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER

📞 **1300 072 926** | globalmachinerysales.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
E sales@globalmachinerysales.com.au
F (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148
E sales@globalmachinerysales.com.au
F (02) 8678 2478



MORBARK BEEVER 1215



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The 18" (45.72cm) diameter single top feed wheel easily climbs over material, reduces drag and increases chipping efficiency.
- Like all Morbark equipment, the 1215 is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labour.



Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



Feed Wheel

TorqMax™ Top Feed Wheel Compression system with spring assisted down pressure generates more than 4,762 kg/m of material pulling force.



New-Style Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed without removing the Beaver from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Chipping capacity 12" (30.5 cm)
 Engine CAT Diesel
 Horsepower 97 HP
 Height 274.3 cm
 Width 180.3 cm
 Length 467.4 cm
 Weight (approximate) 2,358.7 kgs
 Suspension 2,721 kgs
 Infeed opening 60" wide x 31" high
 Throat opening 15" wide x 12" high
 Drum 14.25" wide x 21.375" diameter
 Fuel capacity 92.7 litres
 Hydraulic capacity 64.4 litres
 Frame 3.72 kgs, 15.24 cm channel
 Brakes Electric with breakaway
 Tyres (2) 235/80R16"
 Hitch 63.5 mm Pintle Ring

Equipment Highlights

21.375" diameter x 14.25" wide staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system.
 Reversing automatic feed system.
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment.
 Fuel tank sight gauge and drain plug.
 Hydraulic tank shut-off valve, drain plug and clean-out cover.
 Live hydraulics; ball valve, pump, motor and control valve.
 Tube and support pad to mechanically raise and lower feed wheel using the drawbar jack.
 5" (12.7cm) x 3" (7.6cm) tubular steel telescoping drawbar with two 12" (30.5cm) extensions.

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

Options Include

ChipSafe® Operator Safety Shield



MORBARK



1300 072 926 | globalmachinerysales.com.au