



MORBARK

► **Beever 2021** **TANDEM AXLE** ◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER



📞 **1300 072 926** | globalmachinerysales.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
E sales@globalmachinerysales.com.au
F (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148
E sales@globalmachinerysales.com.au
F (02) 8678 2478

MORBARK BEEVER 2021 **TANDEM AXLE**



BENEFITS

- With its large capacity and high-production volume reduction capabilities, this chipper is perfect for residential tree services, vegetation management, lot and land clearing, maintenance contractors and municipalities.
- The M18R boasts a huge list of options to customize the machine as well as more standard features than any other chipper in its class.
- The unit can be outfitted with a four- or six-cylinder diesel engine and choice of single axle, tandem axle or single axle dual wheel package.
- The dual-sided, chambered air impeller system with controllable air flow vents increases chip-throwing velocity and easy discharge of light, leafy material.
- Like all Morbark equipment, the 2021 is a long-lasting, durable machine backed by a world-class parts and service support team.




TorqMax™ Feed Wheel

The TorqMax™ dual feed wheel compression system provides more than 11,161 kg/m of material pulling force.




Infeed

The 165cm wide x 96.5cm high infeed chute with 78.7cm wide x 52cm high throat opening allows for easy feeding of a variety of materials.



Reversing Auto-Feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum performance.



Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,536 kgs of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Chipping capacity 20" (50.8cm)
 Height 289.5 cm
 Width 231.1 cm
 Length 645.16
 Weight 5,534kgs
 Suspension 3,629kgs leaf
 Infeed opening 65" wide x 38" high
 Throat opening 31" wide x 20.5" high
 Drum 23.5" wide x 37.375" diameter
 Engine CAT Diesel
 Horsepower 250 HP
 Fuel/hydraulic capacity 227/155 litres
 Frame 5 cm x 15.2 cm tubular
 Tyres 235/75R17 1/2"
 Hitch 63.5 mm Pintle Ring

Equipment Highlights

60cm wide x 95cm diameter, four dual-edged knife staggered-pocket drum with patented EZ Drum removable knife holders, dual-sided, chambered air impeller system and controllable air flow vents.

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist and Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle.

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional preplumbed valve section for installation of an aftermarket winch package.

360° manual height-adjustable discharge.

Direct-drive bottom feed wheel.

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

Options Include

ChipSafe® Operator Safety Shield
 Folding infeed tray with spring lift assist
 Winch package: heavy-duty, 2,268 kgs pull capacity with rope and 305 cm chafe guard
 Bottom Bump Bar
 Hydraulic Swivel Discharge
 Cone Holder
 Spare Tyre/Mount
 Folding Infeed Tray
 Flow Control
 Axle Options Available
 Fender Options Available
 Battery Box Options Available
 Custom paint and logo packages



MORBARK



1300 072 926 | globalmachinerysales.com.au