



# MORBARK

## ► Beaver 1621X ◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER



📞 **1300 072 926** | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)

**VIC** 24-28 Williams Road Dandenong Sth. 3175  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)  
**F** (03) 9791 7676

**NSW** Unit 1/21 Penny Place Arndell Park 2148  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)  
**F** (02) 8678 2478

# MORBARK BEEVER 1621X




## BENEFITS

- With its high capacity and lighter weight design, this compact chipper is the ideal unit for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- Like all Morbark equipment, the 1621X is a long-lasting, durable machine backed by a world-class parts and service support team.



### TorqMax™ Feed System

The powerful TorqMax™ top feed wheel compression system generates more than 5,060 kg/m of material pulling force.



### Infeed System

The wide infeed opening with dual infeed rollers with an oversized 18" diameter top feed wheel with straight flow-through infeed easily climbs over material, reduces drag and increases chipping efficiency.



### Channel Frame

Full length channel chassis with cross bracing, this increases structural strength while maintaining low unit weight.



### 360° Hydraulic Chute

Full 360° hydraulic chute with swivel discharge and adjustable height puts chips right where needed without removing the Beever from the tow vehicle.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

### General

Chipping capacity .....	16" (40.64 cm)
Engine .....	CAT Diesel
Horsepower .....	142 HP
Height .....	264.0 cm
Width .....	224.0 cm
Length .....	569.0 cm
Weight (approximate) .....	4,336 kgs
Suspension .....	3,175 kgs
Infeed opening .....	59" wide x 41" high
Throat opening .....	20.5" wide x 18" high
Drum .....	23.8" wide x 30" diameter
Fuel capacity .....	121.13 litres
Hydraulic capacity .....	45.21 litres
Frame .....	3.72 kgs, 15.24 cm channel
Tyres .....	(2) 235/75Rx17 1/2"
Hitch .....	63.5 mm Pintle Ring

### Equipment Highlights

Dual infeed wheel with TorqMax top feed wheel compression system, hydraulic lift assist, spring assisted down pressure and manually applied hydraulic down pressure at the valve handle.

Reversing automatic feed system.

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment.

Fuel tank sight gauge, drain plug and shutoff valve.

Hydraulic tank shut-off valve, drain plug and clean-out cover.

### Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

### Options Include

ChipSafe® Operator Safety Shield  
 Winch package: heavy-duty, 2,268 kgs pull capacity with rope and 305cm chafe guard  
 Custom paint and logo packages  
 Hydraulic Swivel Discharge  
 Cone Holder  
 Spare Tyre/Mount  
 Folding Infeed Tray  
 Bottom Feedwheel  
 Flow Control  
 Axle, Fender and Battery Box Options Available



# MORBARK



1300 072 926 | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)