



MORBARK

▶ MXG50 TRACK ◀◀◀



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER

📞 **1300 072 926** | globalmachinerysales.com.au



VIC 24-28 Williams Road Dandenong Sth. 3175
E sales@globalmachinerysales.com.au

NSW Unit 49-50 Cassola Pl Penrith SW 2750
E sales@globalmachinerysales.com.au

QLD 191 Magnesium Dr, Crestmead QLD
E sales@globalmachinerysales.com.au

MORBARK® MXG50 TRACK



BENEFITS

- This powerful, lightweight and affordable stump grinder is ideal for landscapers, stump grinding contractors and rental stores.
- Its compact size and power — combined with a 50" (127 cm) boom arc swing, maximum cutting height of 21½" (54.6 cm) and maximum cutting depth of 16" (40.6 cm) — allow customers the ability to expand their business or generate new business.
- Equipped with 35 horsepower, this stump grinder gets you on and off the job quickly.
- Like all Morbark equipment, the MXG50 Track is a long-lasting, durable machine backed by a world-class parts and service support team



4-up Fingertip Controls

Tip-out operator's control station with 4-up fingertip controls gives you complete command of the machine functions from one location.



Electric Clutch

Electronic clutch engagement from operator's station increases operator safety and improves belt life.



Boom Pivot Assembly

Heavy-duty boom pivot is enhanced in critical areas for extended service life.



Remote Control

Custom remote control provides full command of the unit from a distance, making the work more efficient, safer and faster.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Length	112" (281.9 cm)
Width	35" (88.9 cm)
Height	54" (137.2 cm)
Weight	862 kgs
Engine	Kohler CH980, 35-HP Petrol
Fuel capacity	34 litres
Hydraulic oil capacity	11.4 litres
Boom arc swing	50" (127 cm)
Maximum cutting height	21½" (54.6 cm)
Maximum cutting depth	16" (40.6 cm)
Tracks	32" (81.3 cm) long x 7" (17.8 cm) wide
Primary drive	V-Belt
Final drive	V-Belt
Cutter wheel speed	1530 RPM
Ground PSI	4.24

Equipment Highlights

50" (127 cm) Boom Arc Swing with Long Boom Technology maintains full width cutting arc regardless of depth with variable swing speed and bolt-on chip containment/deflect curtain.

Two-speed ground travel: 85 FPM for maneuvering around the stump or 160 FPM for traversing to the job.

12.1 CID track drive motors for low-end torque.

1¾" (4.4 cm) diameter, 4140 hardened cutter head shaft with pillow block cutter head bearings.

Steel hood enclosure protecting hydraulic components, fuel and hydraulic reservoirs.

Low-maintenance track system for superior stability over rough or uneven terrain.

Tubular steel frame structure for vibration control and rigidity.

Hydraulic system with dual displacement gear pump, four-spool control valve and geroler drive motors

Morthane® Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

Conventional cutting system with Greenteeth® hardware

Quadwheel® cutter wheel with Wearsharp™ teeth

Custom paint and logo packages



MORBARK



1300 072 926 | globalmachinerysales.com.au