

# BOXER<sup>®</sup>

BY MORBARK<sup>®</sup>

▶ **700HDX DIESEL** ◀◀◀



HEAVY-DUTY SKID STEER LOADERS FROM THE INDUSTRY LEADER

📞 **1300 072 926** | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)



**VIC** 24-28 Williams Road Dandenong Sth. 3175  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)

**NSW** Unit 49-50 Cassola Pl Penrith SW 2750  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)

**QLD** 191 Magnesium Dr, Crestmead QLD  
**E** [sales@globalmachinerysales.com.au](mailto:sales@globalmachinerysales.com.au)

# BOXER 700HDX DIESEL


BY MORBARK®

## Model Specifications

Engine System	US	Metric
Type	Kubota	
Cooling System	Liquid	
HP/kW	24.8 HP	18.5 kW
Fuel Type	Diesel	
Fuel Capacity	9 Gallons	34 Litres
Hydraulic Capacity	24 Gallons	91 Litres
System Flow (Total)	27.1 GPM	103 L/min
Hydraulic Flow Aux (Hi/Lo)	11.3/8.7 GPM	43/33 L/min
Hydraulic Flow (Drive)	7.1 GPM	27 L/min
System Pressure	3000 PSI	20684 kPa
Engine Warranty	2 years	
Product Warranty	1 year	

Units	US	Metric
Track Gauge	33.75 in	857 mm
Track Width	9 in	230 mm
Weight (no attachment)	2860 lbs	1295 kg
Length (w/out Bucket)	77 in	1956 mm
Length (w/Bucket)	96 in	2438 mm
Width (Fully Retracted)	34.5 in	876 mm
Width (Fully Extended)	43.5 in	1105 mm
Height (Overall)	54 in	1372 mm
Height (Fully Raised)	98 in	2489 mm
Operating Capacity (35%)	693 lbs	314 kg
Tip Capacity	1980 lbs	897 kg
Hinge Pin Height (Fully Raised)	77 in	1956 mm
Dump Height	60 in	1524 mm
Dump Angle	37 Degrees	
Ground Clearance	5 inches	127 mm
Ground Speed	4.5 MPH	7.2 km/h
Ground Pressure	4.12 PSI	29.7 kPa

## Model Features



Updated 2/23/17

**BOXER**®  
BY MORBARK®



📞 1300 072 926 | [globalmachinerysales.com.au](http://globalmachinerysales.com.au)